

30Ports C13 15A or 10A Each Outlet



⚡ Input Voltage	⚡ Output Voltage
380V-/3 phase (LLLNG)	220V- WYE
415V-/3 phase (LLLNG)	240V- WYE
433V-/3 phase (LLLNG)	250V- WYE
208V-/3 phase (LLLNG)	228V- Delta(option)
480V-/3 phase (LLLNG)	277V- WYE

Max
45 KW
Total Output Power

Max
63 A
Total Current

30PCS
C13
Socket Standard

⚡ Input Characteristics	
Input Connector	63Ax5wires(or junction box,input breaker optional,price difference,)
Frequency	50/60Hz

🔌 Output Characteristics	
Total Current	Max 63A
Rating Output Voltage	208-250V
Max Output Power for Each Outlet	Under 208V, Max 1310W per Outlet
	Under 220V, Max 1386W per Outlet
	Under 240V, Max 1512W per Outlet
	Under 250V, Max 1575W per Outlet
Total Output Power	Max 45KW
Socket Standard	30pcs C13 (Cen be changed as client request)

⚙️ Protection	
Breaker	Each port with 10A overload protector
Dimension	LxWxH = 1544*91*92mm
Net weight	13KG
Wire specification	UL Certification,with flame retardant function
Certificate	CE FCC RoHS

