

# 4N-POE120-1P

1 Port PoE Extender

4NSYS



## 4N-POE120-1P

Passive 1 Port 10/100M PoE Extender IEEE802.3af 120 Meters POE Repeater for Ethernet Security Systems IP Camera CCTV

### Key Features

- PoE input: 1 RJ45 port
- PoE output: 1 RJ45 port
- Network Medium: Cat5 or better UTP cables (less than 120m/393ft)
- Repeater Mode: Store and forward
- MAC Address Table: 2K
- Packet Buffer Memory: 48 Byte
- Switching Capacity: 400Mbps
- PoE Standard: IEEE 802.3af
- Input power: 13 Watts
- Output power: 12.2 Watts
- Power Supply Type: 1/2+, 3/6-, Mode A, End-Span
- Network Protocol: IEEE 802.3i-10BASE-T, IEEE 802.3u: 100BASE-TX, IEEE 802.3x-Flow Control, IEEE 802.3af-Power over Ethernet;
- Regulation Compliance: FCC Part 15B, ROHS Directive 2011/65/EU, Low Voltage Directive 2014/35/EU, EMC Directive 2004/108/EC;
- Working Temperature: 0°C~40°C / 32 °F~104°F
- Working Humidity: 10%~90%, No Condensation
- Storage Temperature: -30°C~70°C / -22°F~158°F
- Storage Humidity: 5%~90%, No Condensation;
- Dimension: 75x37x26.5mm / 2.95" x 1.46" x 1.04"
- Weight: 52g

4NSYS

WE MAKE YOUR JOB EASIER

4NSYS Co., Ltd.

3F Hana Bldg, 118-2 Oryu-Dong, Guro-Gu, Seoul, Korea, 152100, Korea (South)  
Tel : +82-2-2685-7300 URL : <http://www.4nsystech.com>

