

4N-TY208GP-SFP

L2 WEB Managed Industrial PoE Ethernet Switch



LOOP
PROTECTION



VLAN



6KV LIGHTING
PROTECTION

Product Overview

The 4N-TY208GP-SFP is a full Gigabit L2 WEB managed industrial PoE Ethernet fiber switch independently developed by 4NSYS. It has 8* 10/100/1000Base-T PoE ports(IEEE802.3af/at

FEATURE

Gigabit access, SFP fiber port uplink, Integrated Bypass function

- Support non-blocking wire-speed forwarding.
- Support full-duplex based on IEEE802.3x and half-duplex based on Backpressure.
- Support Gigabit Ethernet port and Gigabit SFP port combination, which enables users to flexibly build networking to meet the needs of various scenarios.
- Support physical single-mode single fiber optical path(Bypass) function, pure hardware switching, short switching time, does not affect the data transmission rate and improves the stability of the network system.

Network management and fast ring function

- STP/RSTP/MSTP.
- Static and dynamic aggregation.
- IEEE802.1Q VLAN, flexible VLAN division, Access, Trunk and Hybrid.
- QoS, Priority mode based on 802.1P, Port & DSCP, queue scheduling algorithm including EQU, SP, WRR & SP+WRR.
- IGMP Snooping V1/V2/V3 meets multi-terminal high-definition video surveillance and video conference access requirements.
- ALC, filter data packet through configuring matching rules, processing operation & time permission, and provide flexible and safe access control.

Security

- 802.1X authentication.
- Port isolation, storm control.
- IP-MAC-VLAN-Port binding.

Stable and reliable

- CCC, CE, FCC, RoHS.
- Low power consumption, No fan, aluminum shell.
- The user-friendly panel can show the device status through the LED indicator of PWR, SYS, Link, L/A.

One-stop remote control and management

- HTTPS, SSLV3, and SSHV1/V2.
- RMON, system log, LLDP, and port traffic statistics.
- CPU monitoring, memory monitoring, Ping test, and cable diagnose.
- Web management, SNMP (V1/V2/V3).

Model	4N-TY208GP-SFP	
Interface Characteristics		
Fixed Port	8* 10/100/1000Base-T PoE ports 2* 100/ 1000Base-X uplink SFP slot ports	
Ethernet Port	Port 1-8 support 10/100/1000Base-T auto-sensing, full/half duplex MDI/MDI-X self-adaption	
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP(\leq 100 meters) 100BASE-TX: Cat5 or later UTP(\leq 100 meters) 1000BASE-T: Cat5e or later UTP(\leq 100 meters)	
SFP Slot Port	Gigabit SFP optical fiber interface, default not include optical modules (optional single-mode / multi-mode, single fiber / dual fiber optical module. LC)	
Wavelength/Distance	multimode: 850nm 0~550M,1310nm 0~2KM single mode: 1310nm 0~40KM , 1550nm 0~120KM	
Chip Parameter		
Network Management Type	L2 (WEB management)	
Network Protocol	IEEE802.3 10BASE-T, IEEE802.3i 10Base-T, IEEE802.3u 100Base-TX IEEE802.3ab 1000Base-X, IEEE802.3z 1000Base-X, IEEE802.3x	
Forwarding Mode	Store and Forward(Full Wire Speed)	
Switching Capacity	20Gbps	
Buffer Memory	14.88Mpps	
MAC	8K	
LED Indicator	PowerIndicatorLight	P: 1 Green
	Fiber Indicator Light	F: 1 Green (Link,SDFED)
	On the PoE seat	Yellow:Indicate PoE
		Green: Indicates network working status

PoE Power	
power supply	DC: 52V/2.3A 120W
PoE power supply method	Supports 1,2+, 3,6-power supply
PoE output power	IEEE802.3af/at, with a maximum power of 30W per port and a total power of 120W
Certification & Warranty	
Lightning Protection	<p>Lightning protection: 6KV 8/20us, Protection level: IP40</p> <p>IEC61000-4-2(ESD):±8kV contact discharge,±15kV air discharge</p> <p>IEC61000-4-3(RS):10V/m(80~1000MHz)</p> <p>IEC61000-4-4(EFT): power cable:±4kV; data cable:±2kV</p> <p>IEC61000-4-5(Surge):power cable:CM±4kV/DM±2kV; data cable:±4kV</p> <p>IEC61000-4-6(radio frequency transmission):10V(150kHz~80MHz)</p> <p>IEC61000-4-8(power frequency magnetic field):100A/m;1000A/m , 1s to 3s</p> <p>IEC61000-4-9(pulsed magnet field):1000A/m</p> <p>IEC61000-4-10(damped oscillation):30A/m 1MHz</p> <p>IEC61000-4-12/18(shockwave):CM 2.5kV,DM 1kV</p> <p>IEC61000-4-16(common-mode transmission):30V; 300V, 1s</p> <p>FCC Part 15/CISPR22(EN55022):Class B</p> <p>IEC61000-6-2(Common Industrial Standard)</p>
Mechanical Properties	<p>IEC60068-2-6 (anti vibration), IEC60068-2-27 (anti shock)</p> <p>IEC60068-2-32 (free fall)</p>
Certification	CCC, CE mark, commercial, CE/LVD EN62368-1, FCC Part 15 Class B, RoHS
Physical Parameter	
Operation TEMP /Humidity	-40~+75°C;5%~90% RH Non condensing
Storage TEMP /Humidity	-40~+85°C;5%~95% RH Non condensing
Dimension (L*W*H)	172mm*145mm*54mm
Installation	Desktop, DIN rail

Network Management Features	
Port configuration	Auto-negotiation Flow Control Port Mirror: TX/RX/BOTH; Many-to-1 monitor Traffic statistics
Link Aggregation	Static link aggregation LACP Algorithm based on Source/Destination MAC Algorithm based on Source/Destination IP
MAC Table	Aging Time Static MAC address Dynamic MAC address management
VLAN	4094 Active VLANs 4094 VID 802.1Q Tag VLAN Port VLAN Protocol VLAN MAC VLAN Voice VLAN 802.1ad Q-in-Q tunneling Private VLAN (Protected port) GARP/GVRP
ACL	256ACLs L2, L3 e L4 Time-based ACL
Spanning tree	802.1D Spanning Tree Protocol (STP) 802.1w Rapid Spanning Tree Protocol (RSTP) 802.1s Multiple Spanning Tree Protocol (MSTP) Loop Guard Root Guard TC-BPDU Guard BPDU Guard BPDU Filter
Multicast	256 groups IGMP v1/v2/v3 Snooping, Fast Leave MLD Snooping Multicast VLAN
QOS	port-based CoS 802.1p-based CoS DSCP-based Scheduling algorithms SP, WRR, SP+WRR Storm Control (Broadcast, Multicast, Unknown Unicast) Bandwidth control per port
DHCP	SNMP v1/v2c/v3 with Full Private MIBs RMON 4 groups WEB (HTTP/HTTPS) upgrade via web/TFTP Configuration Backup/Reload Dual Firmware LLDP

Security Features	<p>Port Security MAC</p> <p>address filter</p> <p>ARP Association (Manual, ARP scanning, DHCP snooping) ARP</p> <p>Protection</p> <p>DoS (Denial of Service)</p> <p>Classification of packages based on: End.MAC, IP End, TCP / UDP Ports, Protocol Type;</p> <p>802.1x Authentication (port-based e MAC-based)</p> <p>TACACS/TACACS+ Authentication</p> <p>RADIUS Authentication</p> <p>DHCP Filter</p> <p>Guest VLAN</p> <p>SSLv2/SSLv3/TLSv1</p> <p>SSHv1/SSHv2</p> <p>Restriction of WEB access based on: IP Address, And. MAC and Port; Port</p> <p>Isolation Loopback detection</p>
Other Features	<p>DNS Client DHCP</p> <p>Relay DHCP Client</p> <p>DHCP Snooping</p> <p>DHCP Option 82</p> <p>SNTP Client</p> <p>UDLD</p>
Maintenance	<p>Cable Diagnostics</p> <p>Ping</p> <p>SFP DDM(Digital Diagnostics Monitoring) Thermal protection</p> <p>System log (Local and Remote)</p> <p>Memory and CPU Monitoring</p>

